

445/95R25 174F CR-01 TL

Asymmetrical non-directional tread pattern designed for mobile crane application. It offers high durability, exceptional operator comfort and low noise emissions in road high speed service. Small blocks tread design offers in OFF-ROAD application excellent traction and self cleaning properties. Increased tyre life due to bridges restricting moving of figure.



Tread pattern depth: 26mm

TYRE SIZE	TREAD PATTERN	LI/SS	TYPE	RIM (PERMITTED)	TYRE DIMENSIONS (mm)					LOAD CAPACITY (kg)	INFLATION (kPa)
					NEW		MAX. IN SERVICE		SR		
					OD	SW	OD	OW			
445/95R25	CR-01	174F	TL	11.00/1.7CR-25 (11.25/2.0-25)	1483	440	1549	483	688	6700	900

VARIATION IN LOAD CAPACITY WITH INFLATION

TYRE SIZE	LI / SS	LOAD CAPACITY PER TYRE (kg)											INFLATION (kPa)
		SPEED (km/h)											
		Static	5	10	20	30	40	50	65	70	80	85	
445/95R25	174F	10 395	8 780	7 575	6 360	5 320	4 900	4 775	4 585	4 475	4 260	4 135	500
		12 125	10 255	8 855	7 430	6 215	5 720	5 570	5 350	5 220	4 970	4 820	600
		13 590	11 465	9 885	8 280	6 915	6 365	6 195	5 950	5 805	5 525	5 360	700
		15 160	12 795	11 035	9 255	7 740	7 125	6 940	6 665	6 510	6 195	6 010	800
		16 750	14 070	12 060	10 050	8 375	7 705	7 505	7 205	7 035	6 700	6 500	900